



## Inductive Sensors Series 30 - NAMUR EN 60947-5-6

Housing M 30 x 1.5

- Housing material: Brass
- For use in areas with the risk of gas explosion, zone 0
- Sensing distance  $S_n = 15$  mm

Certificates:



DMT 03 ATEX E 048



IECEX BVS 07.0031

Ex II 1G Ex ia IIC T1-T6 Ga

Ex ia IIC T1-T6 Ga

### Technical data

Operating distance $S_n$	Non-flush mountable 15 mm
Electrical version	2-wire DC
Output	NAMUR EN 60947-5-6
<b>Type</b>	<b>IAS-30-A24-N</b>
<b>Art.-No.</b>	<b>300 600</b>
Operating voltage ( $U_b$ )	5 - 15 V DC, $U_i = 15$ V DC
Output current active surface free	> typ. 2 mA
Output current active surface covered	< typ. 1.5 mA
Self-inductance (L)	2 mH
Self-capacitance (C)	250 nF
Permitted residual ripple max.	5 %
Frequency of operating cycles max.	1 kHz
Permitted ambient temperature	-25...+70 °C
LED-display	Yellow
Degree of protection IEC 60529	IP 67
Connection cable	2 m PUR, 2 x 0.75 mm <sup>2</sup>
Housing material	Brass
Active surface	PVC
Lid	PA / PPO



Made in Germany

All specifications are subject to change without notice. (05/2013)