



Capacitive Sensors

Series 70 - NPN
Series 80 - PNP



- Housing Ø 30 mm
- Housing material: Brass
 - Sensing distance 0.5...30 mm adjustable


Certificate:




Technical data	Flush mountable
Operating distance S_n	20 mm
Operating distance min. / max. adjustable	0.5...30 mm
Electrical version	4-wire DC
Output function	Antivalent
Type NPN	KAS-70-30-A
Art.-No.	714 200
Connection diagram No.	3
Type PNP	KAS-80-30-A
Art.-No.	814 200
Connection diagram No.	6
Operating voltage (U_B)	10...35 V DC
Output current max. (I_o)	2 x 250 mA
Voltage drop max. (U_d)	≤ 2.0 V
Permitted residual ripple max.	10 %
No-load current (I_o)	Typ. 15 mA
Frequency of operating cycles max.	200 Hz
Permitted ambient temperature	-25...+70 °C
LED-display	Green / yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67*
Norm	EN 60947-5-2
Connection cable	2 m, PVC, 4 x 0.5 mm ²
Housing material	Brass
Active surface	PTFE (FDA 21 CFR 177.1550)
Lid	PA / PPO
Media optimized	Yes

Assessors for mounting (is not delivered with the sensor) please see our selection of accessories.


* With sealed potentiometer screw




1




2




3




4



5



6



Made in Germany

All specifications are subject to change without notice. (06/2014)