



Capacitive Sensors Series 80 - PNP



Housing M 18 x 1

- Housing material: Brass
- Sensing distance 0.5... 15 mm adjustable
- With flange connector M 12 x 1




Certificate:

Technical data	Non-flush mountable
Operating distance S_n	8 mm
Operating distance min. / max. adjustable	0.5...15 mm
Electrical version	4-pin DC
Output function	Antivalent
Type NPN	
Art.-No.	
Connection diagram No.	
Type PNP	
KAS-80-A23-A-Y5	
Art.-No.	
804 091	
Connection diagram No.	
6	
Operating voltage (U_B)	10...35 V DC
Output current max. (I_o)	2 x 250 mA
Voltage drop max. (U_d)	≤ 2.0 V
Permitted residual ripple max.	10 %
No-load current (I_o)	Typ. 15 mA
Frequency of operating cycles max.	50 Hz
Permitted ambient temperature	-25...+70 °C
LED-display	Yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67*
Norm	EN 60947-5-2
Connection	Flange connector M 12 x 1
Housing material	Brass
Active surface	PTFE (FDA 21 CFR 177.1550)
Lid	-
Media optimized	Yes

Accessories (is delivered with the sensor) 2 pieces nuts M 18

For matching connectors please see our selection of accessories.

* With sealed potentiometer screw



All specifications are subject to change without notice. (06/2014)