

## LevelMaster - Capacitive Sensors - S26 - IO-Link



Model G 1/2"

- For level control of conductive and/or viscous liquids or pastes, for instance oil, water, ketchup or honey.
- Ideal for level control in the Food Industry or Pharmaceutical Industry
- Housing material: Stainless steel VA No. 1.4305 (AISI 303)
- Adjustment of the sensitivity with ETW- Function (EasyTeach by wire)
- With flange connector M 12 x 1
- Welding sockets and Varivent adapter available for EHEDG conform mounting.



<b>Technical data</b>	Non-flush mountable
Sensitivity	Dielectric constant $\epsilon_r > 1.25$
Electrical version	3-pin DC
Output function	Normally open
Factory setting	Water
<b>Typ PNP</b>	<b>KS-801-26/86-S-G1/2-PEEK/VAb-IOL-Y3-ETW-HP</b>
<b>Art. No.</b>	<b>KA 1611</b>
Operating voltage ( $U_B$ )	12.5...35 V DC
Voltage drop max. ( $U_o$ )	$\leq 2.0$ V
Operating current ( $I_o$ )	0...250 mA
No-load current ( $I_o$ )	Typ. < 30 mA
Frequency of operating cycles, standard	5 Hz
Frequency of operating cycles, adjustable with IO-Link	3...300 Hz
Permitted ambient temperature	-10...+70 °C / CIP 121 °C
Permitted product temperature	-10 °C...+100 °C
LED-display	Green / orange
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67, IP 69K
Norm	EN 60947-5-2*
Connection	Connector M 12 x 1
Operating pressure	Max. 10 bar
Housing material	Stainless steel VA No. 1.4305 / AISI 303
Material active surface	PEEK (FDA 21 CFR 177.2415)
<b>Accessories</b> (not supplied with the sensor): Varivent Adapter art.No. 196395, Welding Socket art.No. 196394 and matching connectors please see our selection of accessories.	

Capacitive Sensors S26 with hemispherical active surface for level control of products with a dielectric constant  $\epsilon_r$  from 1,25. Products can be:

- Liquids, like water, juice, wine, oil, chemicals or pharmaceutical solutions and much more.

### Highlights:

- EHEDG conform
- Measurement is independent of the mounting position
- Permitted pressure on the active area: 10 bar

### IO-LINK - INTERFACE

Device ID: 2d/000002h  
Vendor ID: 1129d/0469h  
Baudrate: COM 3 (230.4 kbaud)  
Revision: 1.1  
Profil: Smart Sensor  
SIO mode: Yes  
Port Class: A

All specifications are subject to change without notice. (20.12.2021)

\*Where applicable

**EasyTeach chart:** LED / Output function  
Orange = A1 Green = A1

- Adjustment "empty"
- Initializing "empty"
- Adjustment "full"
- Initializing "full"
- Factory reset
- Test

**Made in Germany**

# LevelMaster

EXtra  
Smart

This capacitive sensor is designed for the level control of liquid or viscous products, which can be conductive and/or viscous and sticky.

Materials like ketchup, mayonnaise, yoghurt, syrups, pastes, or liquids with salt or acids will be reliably detected with the LevelMaster.



It could not be easier.

The user mounts the sensor, makes the electrical connection and the adjustment by means of the teach wire and the sensor is ready for use.

No additional teach equipment necessary.

Optical guidance during the teach process with the aid of a 2-colour LED:

• standby • teach process • switching state

The modern micro controller controlled temperature compensation provides for reliable level control with applications where there are variations in the ambient temperatures.

The sensor body is made of stainless steel material No. 1.4305 (AISI 303).

When the sensor is mounted with our adapters: welding socket or the process adapter Varivent N DN 50 a hygienic, EHEDG conforming process connection will be achieved.



Made in Germany