



## Capacitive Sensors Series 80 - PNP

Housing Ø 30 mm

- Housing material: PTFE
- Sensing distance 0.5...30 mm adjustable



### Technical data

	Flush mountable	Flush mountable
Operating distance $S_n$	20 mm	20 mm
Operating distance min. / max. adjustable	0.5...30 mm	0.5...30 mm
Electrical version	3-wire DC	4-wire DC
Output function	Normally open	Antivalent

### Type NPN

#### Art.-No.

Connection diagram No.


### Type PNP

#### KAS-80-30-S-K-PTFE

#### KAS-80-30-A-K-PTFE

Art.-No.	814 620	814 450
Connection diagram No.	4	6
Operating voltage ( $U_b$ )	10...35 V DC	10...35 V DC
Output current max. ( $I_o$ )	400 mA	2 x 250 mA
Voltage drop max. ( $U_d$ )	≤ 2.0 V	≤ 2.0 V
Permitted residual ripple max.	10 %	10 %
No-load current ( $I_o$ )	Typ. 15 mA	Typ. 15 mA
Frequency of operating cycles max.	200 Hz	200 Hz
Permitted ambient temperature	-25...+70 °C	-25...+70 °C
LED-display	Yellow / green	Yellow / green
Protective circuit	Built-in	Built-in
Degree of protection IEC 60529	IP 67	IP 67
Norm	EN 60947-5-2	EN 60947-5-2
Connection cable	2 m, PVC, 3 x 0.75 mm <sup>2</sup>	2 m, PVC, 4 x 0.5 mm <sup>2</sup>
Housing material	PTFE (FDA 21 CFR 177.1550)	PTFE (FDA 21 CFR 177.1550)
Active surface	PTFE (FDA 21 CFR 177.1550)	PTFE (FDA 21 CFR 177.1550)
Lid	PA / PPO	PA / PPO
Media optimized	Yes	Yes

**Assessors** for mounting (is not delivered with the probe) please see our selection of accessories.



**Made in Germany**