



Capacitive Sensors

Series 70 - NPN
Series 80 - PNP










- Housing M 32 x 1.5
- Housing material: PTFE
 - Useable for an ambient temperature up to +100 °C
 - Sensing distance 0.5...30 mm adjustable
 - Ideal for detection of chemically aggressive media
 - Suitable for food applications

Certificate:



Technical data	Flush mountable
Operating distance S_n	20 mm
Operating distance min. / max. adjustable	0.5...30 mm
Electrical version	4-wire DC
Output function	Antivalent
Type NPN	KAS-70-30-A-M32-PTFE-100°C
Art.-No.	715 831
Connection diagram No.	3
Type PNP	KAS-80-30-A-M32-PTFE-100°C
Art.-No.	815 831
Connection diagram No.	6
Operating voltage (U_b)	10...35 V DC
Output current max. (I_e)	2 x 250 mA
Voltage drop max. (U_d)	≤ 2.0 V
Permitted residual ripple max.	10 %
No-load current (I_o)	Typ. 15 mA
Frequency of operating cycles max.	200 Hz
Permitted ambient temperature	-25...+100 °C
LED-display	Green / yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67*
Norm	EN 60947-5-2
Connection cable	2 m, PVC, 4 x 0.5 mm ²
Housing material	PTFE (FDA 21 CFR 177.1550)
Active surface	PTFE (FDA 21 CFR 177.1550)
Lid	PA / PPO
Media optimized	Yes
Accessories (is delivered with the unit)	2 pieces nuts M 32

* With sealed potentiometer screw



Made in Germany

All specifications are subject to change without notice. (06/2014)