



Capacitive Sensors

Series 70 - NPN
Series 80 - PNP

Housing M 12 x 1








- Housing material: Stainless steel VA
- Sensing distance 0.5...5 mm adjustable

Certificate:



Technical data	Flush mountable	Flush mountable
Operating distance S_n	2 mm	2 mm
Operating distance min. / max. adjustable	0.5...5 mm	0.5...5 mm
Electrical version	3-wire DC	4-wire DC
Output	Normally open (NO)	Antivalent
Type NPN	KAS-70-A12-S-NL	KAS-70-A12-A-NL
Art.-No.	KA 0673	KA 0705
Connection diagram No.	1	3
Type PNP	KAS-80-A12-S-NL	KAS-80-A12-A-NL
Art.-No.	KA 0669	KA 0671
Connection diagram No.	4	6
Operating voltage (U_B)	12...30 V DC	12...30 V DC
Output current max. (I_o)	200 mA	2 x 200 mA
Voltage drop max. (U_d)	≤ 2.0 V	≤ 2.0 V
Permitted residual ripple max.	5 %	5 %
No-load current (I_o)	< 15 mA	< 15 mA
Frequency of operating cycles max.	300 Hz	300 Hz
Permitted ambient temperature	-25...+70 °C	-25...+70 °C
LED-display	Yellow	Yellow
Protective circuit	Built-in	Built-in
Degree of protection IEC 60529	IP 67	IP 67
Norm	EN 60947-5-2	EN 60947-5-2
Connection	2 m, PUR, 3 x 0.14 mm ²	2 m, PUR, 4 x 0.14 mm ²
Housing material	VA No. 1.4305	VA No. 1.4305
Active surface	PA / PPO	PA / PPO
Lid	PA / PPO	PA / PPO

All specifications are subject to change without notice. (01.02.2010)



Made in Germany