



Capacitive Sensors
Series 70 - NPN
Series 80 - PNP

Housing M 30 x 1.5








- Housing material: PA / PPO
- Sensing distance 2...20 mm adjustable

Certificate:



Technical data	Flush mountable
Operating distance S_n	10 mm
Operating distance min. / max. adjustable	2...20 mm
Electrical version	4-wire DC
Output	Antivalent (NO + NC)
Type NPN	KAS-70-A14-A-K-NL
Art.-No.	KA 0809
Connection diagram No.	3
Type PNP	KAS-80-A14-A-K-NL
Art.-No.	KA 0808
Connection diagram No.	6
Operating voltage (U_B)	12...30 V DC
Output current max. (I_o)	2 x 200 mA
Voltage drop max. (U_d)	≤ 2.0 V
Permitted residual ripple max.	5 %
No-load current (I_o)	< 15 mA
Frequency of operating cycles max.	150 Hz
Permitted ambient temperature	-25...+70 °C
LED-display	Yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67
Norm	EN 60947-5-2
Connection	5 m, PVC, 4 x 0.5 mm ²
Housing material	PA / PPO
Active surface	PA / PPO
Lid	PA / PPO

All specifications are subject to change without notice. (31.03.2010)



Made in Germany